

### PRODUCT FEATURES

- One component, brush grade product
- Excellent protection against corrosive environments.
- Strong and flexible
- Withstands expansion and contraction
- Seals and waterproofs
- Resists cracking and peeling
- Commercial Grade Product

### TYPE OF APPLICATIONS

- Fasteners, Flashings & Gutters
- Metal Buildings & Roofs
- Modified & BUR Roofs
- Polyurethane Foam & Concrete Surfaces or Roofs
- Single Ply Roofs
- Industrial Roofs



**SURFACE PREPARATION:** The surface must be free of any oils, moisture, rust scale, soil or other contaminants that may interfere with good adhesion. Remove any loose material from seams or other surfaces with a wire brush or scraper. Oil and grease should also be removed with solvents or an appropriate cleaner, such as Inland's RC-300.

In many cases, high pressure water blasts will be sufficient to prepare the surface.

### APPLICATION

**TEMPERATURE:** For best results, the temperature of the ambient air and the substrate should be within a range of 40° - 110°F. Although lower temperatures can be used for brush applications, it is recommended that the product temperature be a minimum of 70°F when pumping the product.

**APPLICATION METHODS:** Pro Repair can be brushed, rolled or pumped onto the surface. Apply heavy, uniform coats over fasteners, seams etc...to ensure maximum coverage.

## TECHNICAL DETAILS

### SYNTHETIC RUBBER

type of resin

400%

elongation

ZERO

reduction

### WHITE & GRAY

available colors

1,000 PSI

tensile strength

101°F

flashpoint

0.94

specific gravity

60.1

solids (%/weight)

12,000

Viscosity

7.86

weight (lb/gal)

53.1

solids (%/vol)

436

VOC (grams/liter)