

**IN-BULL PC** Plastic Cement**DESCRIPTION:**

In-Bull PC Roof Cement is an all purpose asphalt mastic for sealing, repairing and installing asphalt based roofing. It meets the ASTM D-4589 TYPE I requirements.

**SUITABLE SUBSTRATES:**

- Granulated BUR
- Smooth BUR
- Asphalt Shingles
- Metal Flashings
- Masonry

**INSTALLATION INSTRUCTION:**

**SURFACE PREPARATION:** The surface must be free of any oils, moisture, rust scale, soil or other contaminants that may interfere with good adhesion. Remove any loose material from seams or other surfaces with a wire brush or scraper. Oil and grease should also be removed with an appropriate cleaner. In many cases high pressure water blast will be sufficient to prepare the surface.

**APPLICATION INSTRUCTIONS:** Apply only when ambient temperatures are 50°F and rising, and substrate temperatures do not exceed greater than 130°F. Apply the product evenly with a pointed roofer's trowel or gloved hand. The product should be applied 1/8 to 1/4 of an inch thick and may be reinforced with polyester fabric to strengthen the repair. When making a permanent repair to a blister, open up the area and allow it to dry thoroughly prior to making the repair.

**PACKAGING:**

3-gal metal pail	30 lbs.	60-per pallet
5-gal metal pail	50 lbs.	36-per pallet

**TECHNICAL DATA:**

Viscosity @ 78°	800,000 cps
Solids (% by weight)	75%
Weight (lb./gal.)	9.8 lbs
VOC Content	< 250 g/l
Flashpoint	103°F
Shelf Life	24-months
Standard Color(s)	Black

**PRECAUTIONS:**

**PREVENTION:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed when product is not in use. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting/equipment.

**RESPONSE:** IF exposed or concerned: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. In case of fire: Use CO2, dry chemical, or foam for extinction.

**OTHER INFORMATION:** May be harmful if swallowed. May be harmful in contact with skin. Toxic to aquatic life with long lasting effects. Unknown acute toxicity 35% of the mixture consists of ingredient(s) of unknown toxicity.

**STORAGE & HANDLING PROCEDURES:**

Store locked up. Store in a well-ventilated place. Keep cool. Shelf life is 24-months if stored in original unopened containers. Store between 45°F and 95°F. Do not allow product to freeze. Do not heat with an open flame. All containers must be sealed when not in use. Wear protective gloves, protective clothing, eye protection, and face protection. If exposed or concerned: Get medical advice or attention. Clean equipment and any over-spray with water. A hand soap and water will clean hands.

**WARRANTY & DISCLAIMER:**

Inland Coatings, Inc. (Inland) warrants that this product conforms to the published product specifications as of the date of manufacture. Inland does not make, nor does it authorize anyone to make, any warranty of merchantability or fitness for any purpose, or any other warranty, guarantee, or representation. INLAND HEREBY DISCLAIMS ANY AND ALL EXPRESS, IMPLIED, OR STATUTORY WARRANTIES. The sole obligation of the manufacturer, distributor, and/or seller of this product shall be the replacement of product proven to be defective in manufacturing if written notice is received within one year of the date of purchase. There shall be no liability for injury, loss, or damages, either direct or consequential, arising out of the use or inability to use this product. Failure to notify the manufacturer prior to remedy or resolution voids the warranty and the manufacturer's liability.