

RST Roofing Seam Tape - Butyl Adhesive**DESCRIPTION:**

RST Butyl Seam Tape is a high-performance butyl adhesive tape with instant aggressive adhesion to most substrates. RST Butyl Seam Tape has a fabric backing that allows for excellent adhesion of Inland Coatings' Roof Coatings. RST Butyl Seam Tape provides increased protection against water penetration in all roof systems that contain areas that require such, including but not limited to, panel gaps on metal roofs, seams on single-ply roofs, and various roof penetrations.

SUITABLE SUBSTRATES:

- EPDM
- PVC
- Hypalon
- TPO
- BUR (asphalt)
- Modified Bitumen
- Metal
- New Spray Polyurethane Foam

INSTALLATION INSTRUCTIONS:

SURFACE PREPARATION: The surface must be free of any oils, moisture, rust scale, soil or other contaminants that may interfere with good adhesion. All previous repair material must be removed from seams or other surfaces. In many cases high pressure water blast will be sufficient to prepare the surface.

APPLICATION INSTRUCTIONS: Apply only when ambient temperatures are 35°F and rising, and substrate temperatures do not exceed greater than 110°F. Cut desired length, peel off release liner and apply. Removal or repositioned may damage product and surface. Overlap at ends. Use squeegee with heavy pressure to assure complete contact.

PACKAGING:

RST-200 - Roll	2" x 50'	24 Per Box
RST-400 - Roll	4" x 50'	12 Per Box

TECHNICAL DATA:**VALUE:**

Total Thickness	25-29 Mils
Adhesive Type	Modified Butyl
Adhesive Side	Single Sided
Peel Adhesion	>10 pli
Bonding Time	Immediate, Aggressive Grip, Full Bond within 24-hours
Tensile Strength	790 psi min.
Recommended Application Temperature	35°F - 110°F
Service Temperature	-20°F - 180°F
Elongation	560% Average
VOC Limitation	Pass
VOC	Pass
Cold Temperature Flexibility	Pass
Adhesion to Coatings	Excellent
Odor	Neutral
Standard Color	White

PRECAUTIONS:

- Do not use where alkaline chemicals are present.
- Do not use in areas where surface temperature will exceed 180°F.
- Do not stretch.
- Product is not repositionable.

HANDLING & STORAGE PROCEDURES:

Shelf life is 24-months if stored in original unopened containers. Store between 45°F and 95°F. Do not allow product to freeze. Do not heat with an open flame. Wear protective gloves, protective clothing, eye protection, and face protection.

WARRANTY & DISCLAIMER:

Inland Coatings, Inc. (Inland) warrants that this product conforms to the published product specifications as of the date of manufacture. Inland does not make, nor does it authorize anyone to make, any warranty of merchantability or fitness for any purpose, or any other warranty, guarantee, or representation. INLAND HEREBY DISCLAIMS ANY AND ALL EXPRESS, IMPLIED, OR STATUTORY WARRANTIES. The sole obligation of the manufacturer, distributor, and/or seller of this product shall be the replacement of product proven to be defective in manufacturing if written notice is received within one year of the date of purchase. There shall be no liability for injury, loss, or damages, either direct or consequential, arising out of the use or inability to use this product. Failure to notify the manufacturer prior to remedy or resolution voids the warranty and the manufacturer's liability.

